





# H-79



**Product:** Oil based degreasing agent.

**Properties:** H-79 is a highly effective degreasing agent particularly for the removal of oil, tar and asphalt. This popular degreasing agent is specially developed for industrial use. It is the perfect solution to clean machines and machine parts. Removes asphalt stains from vehicles before wash.

**Usage:** Use undiluted. Apply with an atomizer or brush. Machine parts can be laid down in to the solvent. Immediate effect or leave for up to 5 minutes for full efficiency. Do not let the solvent dry. If necessary, rinse with water.

**Storage:** Store in tightly closed original container. Keep in a non-freezing place. Store securely and keep out of the reach of children.

**Safety:** Please find information about handling and disposal in the Safety Data Sheet.

*The Safety Data Sheet can be accessed here: [www.kemilux.com](http://www.kemilux.com)*

**INSTR. FOR USE AND DOSAGE**  
 DOSAGE: Undiluted  
 TAKE EFFECT: immediate effect  
 maximum 5 minutes +

**PRODUCT DATA**  
 APPEARANCE: Clear, slightly brown liquid  
 STATE: Liquid  
 ODOUR: Turpentine  
 DENSITY G/ML: 0,79

*For less demanding tasks H-80 is recommended*

## H-79 is recommended for:

- Machine parts
- Metal surfaces
- Softening asphalt stains



**DANGER**

PACKAGING: 1L, 5L, 10L, 20L, 210L, 1000L

# KEMILUX